



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Takayuki SAWADA *et al.*
Title: COLOR IMAGE PROCESSING APPARATUS AND
COLOR IMAGE FORMING APPARATUS
Appl. No.: Not yet assigned
Filing Date: August 25, 2000
Examiner: Not yet assigned
Art Unit: Not yet assigned

UTILITY PATENT APPLICATION
TRANSMITTAL

Assistant Commissioner for Patents
Box PATENT APPLICATION
Washington, D.C. 20231

Sir:

Transmitted herewith for filing under 37 C.F.R. § 1.53(b) is the nonprovisional utility patent application of:

Takayuki SAWADA
Shinsaku ITO

Enclosed are:

- [X] Specification, Claim(s), and Abstract (44 pages).
- [X] Formal drawings (7 sheets, Figures 1-13)
- [X] Declaration and Power of Attorney (2 pages)
- [X] Associate Power of Attorney
- [X] Assignment to TOSHIBA TEC KABUSHIKI KAISHA
- [X] Assignment Recordation Form Cover Sheet
- [X] Information Disclosure Statement
- [X] Form PTO-1449 and 2 references
- [X] Claim for Convention Priority.
- [X] Certified copy of priority document (Japanese Patent Application No. 11-242119, filed August 27, 1999).



096443389 082500

The filing fee is calculated below:

	Claims as Filed		Included in Basic Fee		Extra Claims		Rate		Fee Totals
Basic Fee							\$690.00		\$690.00
Total Claims:	18	-	20	=	0	x	\$18.00	=	0.00
Independents:	4	-	3	=	1	x	\$78.00	=	\$78.00
If any Multiple Dependent Claim(s) present:						+	\$260.00	=	0.00
Assignment Recordation Fee						+	\$40.00	=	\$40.00
							SUBTOTAL:	=	\$808.00
[]							Small Entity Fees Apply (subtract 1/2 of above):	=	\$0.00
							TOTAL FILING FEE:	=	\$808.00


- [X] A check to cover the \$808.00 filing fee is enclosed.
- [] The required filing fees are not enclosed but will be submitted in response to the Notice to File Missing Parts of Application.
- [X] The Assistant Commissioner is hereby authorized to charge any additional fees which may be required regarding this application under 37 C.F.R. §§ 1.16-1.17, or credit any overpayment, to Deposit Account No. 19-0741. Should no proper payment be enclosed herewith, as by a check being in the wrong amount, unsigned, post-dated, otherwise improper or informal or even entirely missing, the Assistant Commissioner is authorized to charge the unpaid amount to Deposit Account No. 19-0741.

Please direct all correspondence to the undersigned attorney at the address indicated below.

Respectfully submitted,

Date: August 25, 2000

By

 Reg No 26874

FOLEY & LARDNER
3000 K Street, N.W., Suite 500
P.O. Box 25696
Washington, D.C. 20007-8696
Telephone: (202) 672-5300
Facsimile: (202) 672-5399

Johnny A. Kumar
Attorney for Applicant
Registration No. 34,649

005220" 68534350

TITLE OF THE INVENTION

COLOR IMAGE PROCESSING APPARATUS AND COLOR IMAGE
FORMING APPARATUS

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is based upon and claims the
benefit of priority from the prior Japanese Patent
Application No. 11-242119, filed August 27, 1999, the
entire contents of which are incorporated herein by
reference.

10 BACKGROUND OF THE INVENTION

 The present invention relates to a color image
processing apparatus, and more particularly, to a color
image processing apparatus which adjusts parameters for
image processing, using a patch image.

15 Image forming apparatuses, such as copying
machines and printers, have recently been adapted to
mainly do color printing. Accordingly, print color is
required to have precisely specified gradation
characteristics. For example, a copying machine
20 performs color conversion to convert RGB image data
input from a scanner to CMY image data to be output on
a printer using color material. To duplicate an image
so that the original tone of color is faithfully
reproduced, color conversion characteristics (color
25 conversion parameters and a color conversion table)
must be adjusted properly.

 To duplicate a color image faithfully, gradation

005280" 6854960

characteristics must also be adjusted properly. When passing through a sensor or a filter, image data input from a scanner suffers distortion for R, G, and B. When a printer is provided with the same image data, images which differ in gradation and color are output from time to time due to different environments (different temperatures and humidities), time-dependent changes, and differences between individual products. Especially because the gradation characteristics of a printer sensitively change in response to various factors, a mechanism which properly adjusts the output gradation characteristics and color conversion characteristics of the printer must be installed in the printer to keep reproducing an image well.

A method for determining color conversion parameters is known which collects multicolor patch RGB-CMY data pairs by making an apparatus to read a color patch sample output therefrom and finds by the least-square method the coefficient of each term of a polynomial for converting RGB data to CMY data. The method, which considers image processor characteristics other than color conversion to be like a black box, is based on the idea that ideally, an image can be reproduced faithfully only by color conversion, because black box inverse corrections are made using color conversion.

A method is also known which color conversion

parameter setting are fixed under an assumption and adjusts output gradation characteristics in the same way as described above. That is, the method collects multigradation patch C', -C, M', -M, Y', and -Y data pairs by making an apparatus to read a color patch sample output therefrom and finds by the least-square method the coefficient of each term of gradation correction equations for C, M, and Y.

However, it is difficult to output an image with satisfactorily reproduced gradation and color even using the above-described adjusting methods. This is because image processing performed by equipment from a scanner to a printer comprises the steps of color conversion, blackening, gradation processing (quasi intermediate gradation processing), screen processing, etc. in which image data suffers nonlinear distortion with different characteristics.

Thus a problem with conventional image forming apparatuses is that it is difficult to generate all parameters at a time which are used for correcting nonlinear distortion due to color conversion, blackening, gradation processing, screen processing, etc.

Another problem with conventional equipment is that it is difficult to correctly estimate record gradation for characteristics of individual equipment and incorporate the estimated record gradation into

5

10

15

20

25

or the like. By doing so, tables for correcting image processing, taking into account a gradation characteristic tendency unique to equipment are created, thus providing a color image processing apparatus which makes it possible to make fine gradation corrections for individual equipment.

According to the present invention, a color image processing apparatus comprising: first patch image output means for outputting first patch image data on the basis of the first patch data for creating a pulse width selection table stored in the first storage area; first patch data extracting means for reading, using a scanner, a first patch image represented by first patch image data output by the first patch image output means, and for extracting first patch data in accordance with the first patch image; first gradation estimating means for estimating the record gradation of the first read patch data, from on the first read patch data extracted by the first patch data extracting means; pulse width selection table setting means for setting a pulse width selection table on the basis of the record gradation of the first read patch data estimated by the first gradation estimating means and the first patch data; second patch image output means for outputting second patch image data, using the pulse width selection table set by the pulse width selection table setting means and on the basis of the second patch data for creating

a gradation correction table stored in the second storage area; second patch data extracting means for reading, using a scanner, a second patch image represented by second patch image data output by the
5 second patch image output means, and for extracting second patch data in accordance with the second patch image; second gradation estimating means for estimating the record gradation of the second read patch data on the basis of the second read patch data extracted by
10 the second patch data extracting means; gradation correction table setting means for setting a gradation correction table on the basis of the record gradation of the second read patch data estimated by the second gradation estimating means and the second patch data;
15 third patch image output means for outputting third patch image data, using the pulse width selection table set by the pulse width selection table setting means and the gradation correction table set by the gradation correction table setting means and on the basis of the
20 third patch data for creating a color conversion table stored in the third storage area; second patch data extracting means for reading, using a scanner, a third patch image represented by third patch image data output by the third patch image output means, and for
25 extracting third patch data according to the third patch image; color conversion table setting means for setting a color conversion table on the basis of the

third read patch data extracted by the third patch data
extracting means and the third patch data; and
correction output means for correcting a given and
input color image signal on the basis of the pulse
width selection table set by the pulse width selection
5 setting means, the gradation correction table set by
the gradation correction table setting means, and the
color conversion table set by the color conversion
table setting means, and for outputting the corrected
10 signal.

According to the present invention, based on
gradation estimated in such a way, image processing
tables, that is, pulse width selection, gradation
correction, and color conversion tables are created one
15 after another. By doing so, the adjustable parameter
tables can be dispersively provided at a plurality of
key points in an image processing flowchart to create
each table according to a relatively simple target or
rule, so that a color image processing apparatus can be
20 provided which feeds a color image with well-reproduced
gradation and color.

Additional objects and advantages of the invention
will be set forth in the description which follows, and
in part will be obvious from the description, or may be
25 learned by practice of the invention. The objects and
advantages of the invention may be realized and
obtained by means of the instrumentalities and

combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate presently preferred embodiments of the invention, and together with the general description given above and the detailed description of the preferred embodiments given below, serve to explain the principles of the invention.

FIG. 1 is a block diagram illustrating a configuration of an image processor according to the present invention.

FIG. 2 is a block diagram illustrating a configuration of a patch data processor according to the present invention.

FIG. 3 a block diagram illustrating another configuration of the patch data processor according to the present invention.

FIG. 4 is a block diagram illustrating an example of an image forming apparatus using an image processing apparatus according to the present invention.

FIG. 5 is flowchart generally illustrating execution of the present invention.

FIG. 6 is a flowchart for creating a pulse width selection table.

FIG. 7 is a flowchart for creating a gradation correction table.

FIG. 8 is a flowchart for creating a color conversion table.

FIG. 9 is a plan view showing patch images for creating a pulse selection table and a gradation correction table.

FIG. 10 illustrates data sampling from one patch.

FIG. 11 is a graph showing an example of a relationship between the area rate calculated by polynomial approximation and pulse width.

FIG. 12 is a graph showing an example of a relationship between the area rate calculated by polynomial approximation and 8-bit gradation level.

FIG. 13 is a plan view showing an example of patch image for creating a color conversion table.

DETAILED DESCRIPTION OF THE INVENTION

Referring now to the drawings, embodiments of the present invention are described below.

<Configuration and operation of image processor>

Below are described a configuration of an image processor 36 which corrects characteristics, using a patch image characterizing the present invention and characteristic correction by the processor.

FIG. 1 is a block diagram illustrating the configuration of the image processor according to the present invention. As shown in FIG. 1, the image processor according to the present invention, which is connected with a color scanner 1 and color printer 2

when used, consists of the following components
connected together: an image processing controller 51,
a preprocessor 52, a patch data extractor 53, a color
conversion table setting unit 54, patch data memory
5 C 56, a patch data creator C 57, a color converter 58,
a blackening unit 59, a gradation correction table
setting unit 60, a gradation corrector (output γ
corrector) 61, patch data memory B 62, a patch image
creator B 63, a quasi intermediate gradation processor
10 64, a pulse width selection table setting unit 65,
patch data memory A 66, a pulse width selector 67, a
patch image creator A 68, a screen processor 69, and a
patch data processor 70, or the hub of the present
invention.

15 The function of each component is described
according to a ordinary flow of data as observed when
an image is duplicated by a digital copying machine
using the image processor. At first, the RGB image
data on an original read by the color scanner 1 is
20 input to the preprocessor 52. The preprocessor 52
makes shading and input γ corrections to the image data
fed from the scanner. The color converter 58 converts
the input image data, expressed by RGB color space, to
image data expressed by CMY color space. The
25 blackening unit 59 calculates the amount of black-color
material (K) from the CMY data (blackening material
creation) and corrects the amount of CMY according to

the value of K (black-color replacement). After blackening, the output γ corrector 61 makes a gradation correction to the CMY image data for each color channel. The quasi intermediate gradation processor 64 performs

5 quasi intermediate gradation processing, such as multivalue error expansion. For example, a 16-value recording system performs 16-value error expansion. In this case, each image data pixel output only takes 16 values from 0 to 15, expressed using 4 bits. The pulse

10 width selector 67 selects the pulse width of a recording laser drive signal for each of levels 0 to 15. The screen processor 69 converts the image data, converted to a pulse width signal, to a recording pattern which is given a screen angle for each color

15 channel. The color printer (recording engine) 2 outputs the image subjected to screen processing onto paper. Other blocks in FIG. 1 are described below together with table creation.

<Structure of digital copying machine using image processor>

20

The structure and operation of a digital copying machine is described below which uses the above-described image processor of the present invention. FIG. 4 is a block diagram schematically illustrating

25 electrical connections and a control signal flow in a digital copying machine according to the present invention. In FIG. 4, a control system consists of

three CPUs: a main CPU (central processing unit) 91 in a main controller 30, a scanner CPU 100 in the color scanner 1, and a printer CPU 110 in the color printer 2.

5 The main CPU 91 has bi-directional communicates through common RAM (random access memory) with the printer CPU 110. The main CPU 91 issues an operational direction to the printer CPU, and the printer CPU 110 returns a status to the main CPU. The printer CPU 110 and scanner CPU 100 have serial communications with
10 each other. The printer CPU issues an operational direction to the scanner CPU, and the scanner CPU 100 returns a status to the printer CPU.

An operation panel 40, which has a liquid crystal display 42, operation keys 43, and a panel CPU 41
15 connected with the display and keys, is connected with the main CPU 91.

The main controller 30 consists of the main CPU 91, ROM (read-only memory) 32, RAM 33, NVRAM 34, the common RAM 35, the image processor 36, a page memory
20 controller 37, page memory 38, a printer controller 39, and printer font ROM 121.

The main CPU 91 controls the entire system. A control program and the like are stored in the ROM 32. The RAM 33 temporarily stores data.

25 The NVRAM 34, nonvolatile random access memory backed up by a battery (not shown), maintains stored data if the power is turned off.

The common RAM 35 is used for bi-directional communications between the main CPU 91 and printer CPU 110.

5 The page memory controller 37 stores image information in the page memory 38 and reads it therefrom. The page memory 38 with an area sufficient to store a plurality of pages of image information is adapted so that data into which image data from the color scanner 1 is compressed can be stored for each
10 page.

Font data corresponding to print data is stored in the printer font ROM 121. The printer controller 39 expands print data from external equipment, such as a personal computer, into image data at a resolution
15 equivalent to resolution data included in the print data, using font data stored in the printer font ROM 121.

20 The color scanner 1 comprises the scanner CPU 100, which controls the entire system; ROM 101 in which a control program and the like are stored; RAM 102 for storing data; a CCD driver which drives a color image sensor 15; a scanning motor driver 104 which controls rotation of a scanning motor moving a first carriage; and an image corrector 105.

25 The image corrector 105 comprises an analog-digital converting circuit which converts R, G, and B analog signals output from the color image sensor 15 to

digital signals, a shading correcting circuit which corrects variations in the threshold level relative to an output signal from the color image sensor 15 due to color image sensor 15 variations, an ambient
5 temperature change, or the like, and line memory which temporarily stores a digital signal subjected to shading correction which is fed from the shading correction circuit.

The color printer 2 comprises the printer CPU 110
10 which controls the entire system, ROM 111 in which a control program and the like are stored, RAM 112 for storing data, a laser driver 113 which drives a semiconductor laser oscillator 60, a polygon motor driver 114 which drives a polygon motor 54 of an
15 exposure apparatus 50, a transfer controller 115 which controls transfer of paper P by a transfer mechanism 20, a process controller 116 which controls a process of charging, development, and transcription performed using a charging apparatus, a developing roller, and a
20 transfer apparatus, a fixation controller which controls a fixing apparatus 80, and an option controller 118 which controls an option.

The image processor 36 which has a function characterizing the present invention, page memory 38,
25 printer controller 39, image corrector 105, and laser driver 113 are connected together using an image data bus 120.

<Processing performed by image processor using patch image>

Referring now to the drawings, processing which is performed by an image processor of the present invention, using a patch image is described below.

FIG. 5 is a flowchart illustrating a series of steps in which image processing parameter tables of the present invention are created.

In an embodiment of the present invention, the above-described image processor creates the pulse width, gradation correction, and color conversion tables in the order shown in FIG. 5. That is, first, preprocessing input γ characteristics are made linear (S11), and then the pulse width selection table is created using, for example, a patch table (S12). Next, the gradation correction table is created based on the pulse width selection table obtained, using a patch image, for example (S13). Finally, the color correction table is created based on the gradation correction table obtained, using, for example, a patch image (S14). In the embodiment, the tables are sequentially created, one which has the lowest degree of freedom and can be created according to the simplest policy first, and moreover, the following table is based on the preceding table. This allows an input image to be reproduced correctly although a simple creating method does not.

Referring to a flowchart, steps in which the three tables are created using patch images are described in detail below.

FIG. 6 shows a pulse selection table creating flowchart. First, a patch image for creating a pulse width selection table is output (S21). Patch data for creating a pulse width selection table is stored in patch data memory A 66. The patch data, representing pulse widths, is set so that a plurality of patches are laid out which are provided by changing the pulse widths at regular intervals for C, M, Y, and K. The patch image creator A 68 creates patch image data for creating a pulse width selection table, using the patch data. FIG. 9 shows an example of a patch image configuration. The patch image data is fed to the screen processor 69 (S22). In response to a control signal from the image processing controller 51, the screen processor 69 selects image data from the patch image creator A 68 as input. After subjected to screen angle processing, the patch image data is output onto paper (S23).

The output patch image for creating a pulse width selection table is read by the scanner 1 (S24). In this case, using the image processing controller, the input γ characteristics of the preprocessor 52 are changed so that they are linear, not as usual (S25). The reason why this step is taken is as follows. It is

desirable that patch data read be directly proportional to the quantity of light reflected from a patch image to estimate record gradation (for example, the are rate) from the patch data read using a patch data processor 70, described later. However, it is sometimes desirable that the input γ characteristics be directly proportional to a power of the quantity of light reflected. After subjected to preprocessing, patch image data input from the scanner is fed to the patch data extractor 53. Based on preset information on patch print layout, the patch data extractor 53 samples pixel data to extract the R, G, and B values of each patch (S26). To cancel the effect of noise, many pixels in rectangular formation are cut out of the middle of a patch, and the total of them is calculated. Each of the R, G, and B values is divided by the number of pixels cut to take an average (see FIG. 10).

From the extracted patch data, the record gradation of the patch image is estimated (S27).

Record gradation can be estimated by various methods. For example, at least three methods are conceivable. The first method finds the C, M, Y, and K area rates, the second finds both record area rate and record density and selects either as required, and the third sets a plurality of levels of record gradation and estimates gradation, referring to a reference table which is created for each record gradation level. In

addition, various modified methods are available.

First, a method which finds the record area rate is described below. The C, M, Y, and K record area rates of a patch image are estimated using the following:

$$\left. \begin{aligned} C &= 255 - R \\ M &= 255 - G \\ Y &= 255 - B \\ K &= 255 - (R + G + B) / 3 \end{aligned} \right\} \dots (1)$$

where R, G, B, C, M, Y, and K are each expressed using eight bits.

Finally, the pulse width selection table setting unit creates a pulse width selection table, based on the estimated area rate and patch data which is stored in the patch data memory A. The relationship between the estimated area rate and pulse width is approximately found as the polynomial of n-th degree named Expression 2 (S28). The least-square method is used to calculate coefficients a_k in Expression 2.

$$P = \sum_{k=0}^n a_k x^k \dots (2)$$

(x: area rate, p: pulse width)

FIG. 11 shows an example of a curve representing the relationship between the estimated area rate and pulse width. Pulse selection table values are calculated by dividing the area rate axis into as many equal segments as recorded values (for 16-value error expansion, the axis is divided into 16 equal segments) and finding the

pulse width corresponding to each division point using Expression 2 (S29).

Although the number of gradation levels is limited to, for example, 16, a pulse width selection table is
5 created according to a simple, easy-to-keep rule that a laser drive pulse width is assigned so that the record area rate linearly changes for each level (that is, each of the limited number of gradation levels represents an area rate), as described above. This
10 makes it possible to keep good gradation resolution over the entire density range, thus reproducing gradation without density breaks or density skips.

Below is described the way to find both record area rate and record density and select either as
15 required. FIG. 2 shows an example of the patch image processor 70, which consists of a density estimator 71, an area rate estimator 72, and a selector 73 which receives output from the density estimator and area rate estimator and selects the record area rate or
20 record density as specified by a gradation estimating method specifier 74. For this configuration, processing performed by the density estimator 71 is represented by the following:

$$\begin{aligned} C &= -\log_{10}(r / 255) \\ M &= -\log_{10}(G / 255) \\ Y &= -\log_{10}(B / 255) \\ K &= -\log_{10}[(R + G + B) / 3 / 255] \end{aligned} \quad \dots (3)$$

25

where R, G, B, C, M, Y, and K are each expressed using

eight bits.

The selector 73 selects the estimated density obtained using the above-described equation and estimated area rate as specified by the gradation estimating method specifier 74.

Then the pulse width selection table setting unit 65 sets a pulse width selection table in the same way as described above.

Using FIG. 3, below is described the way to set a plurality of levels of record gradation and estimate gradation, referring to a reference table which is created for each record gradation level. As shown in FIG. 3, first and second gradation estimators 81 and 82 each have a first gradation estimating reference table 85, first table setting means 86 which make settings in the first gradation estimating reference table, a second gradation estimating reference table 83, and second table setting means 84 which make settings in the second gradation estimating reference table. The selector receives output from the first and second gradation estimators and outputs either as specified by the gradation estimating method specifier 88.

The first and second gradation estimators 81 and 82 may be the above-described density estimator 71, area rate estimator 72, or other record gradation estimating means. The gradation estimating reference tables 85 and 83 can be set at will by the gradation

table setting units 86 and 84. Such a configuration makes it possible to provide an image processor materializing a digital copying machine with higher gradation reproducibility by switching between a plurality of gradation estimators according to use condition.

Using the gradation correction table creating flowchart in FIG. 7, a procedure for setting a gradation correction table is described below. First, a patch image for creating a gradation correction table is output. Patch data for creating a gradation correction table is stored in the patch data memory B 62. The patch data, representing 8-bit gradation levels to be fed to the quasi intermediate gradation processor 64, is set so that a plurality of patches are laid out which are provided by changing the gradation levels at regular intervals for C, M, Y, and K. The patch image creator B 63 creates patch image data for creating a gradation correction table, using the patch data (S31). The layout of patch images is almost the same as in FIG. 9. The patch image data is fed to the quasi intermediate gradation processor 64. In response to a control signal from the image processing controller 51, the quasi intermediate gradation processor 64 selects image data from the patch image creator B 63 as input. After subjected to quasi intermediate gradation processing (S32), pulse width

selection using the above-described set pulse width selection table (S33), and screen angle processing (S34), the patch image data is output onto paper (S35).

5 The output patch image for creating a gradation correction table is read by the scanner (S36). In this case, using the image processing controller 51, the input γ characteristics of the preprocessor 52 are changed so that they are linear, not as usual. The reason is the case with the above-described pulse width
10 selection table creation. Patch image data input from the scanner is fed through the preprocessor 52 to the patch data extractor 53 (S37). Based on preset information on patch print layout, the patch data extractor 53 samples pixel data to extract the R, G,
15 and B values of each patch (S38). To cancel the effect of noise, many pixels in rectangular formation are cut out of the middle of a patch, and the total of them is calculated. Each of the R, G, and B values is divided by the number of pixels cut to take an average
20 (FIG. 10).

 From the extracted patch data, the record gradation of the patch image is estimated (S39). As described above, at least three methods for estimating record gradation, including those of FIGS. 2 and 3, are
25 available: the first method which finds C, M, Y, and K area rates, the second which finds both record area rate and record density and selects either as required

(see FIG. 2), and the third which sets a plurality of levels of record gradation and estimates gradation, referring to a reference table created for each record gradation level. In addition, as is the case with pulse width selection table setting, various methods are possible, including steps extracted from those methods (for example, a step of estimating record density only) and combinations of the steps.

Finally, the gradation correction table setting unit creates a gradation correction table, based on the estimated record gradation (for example, the area rate) and patch data which is stored in the patch data memory B (S41). The relationship between the estimated area rate and 8-bit output gradation level is approximately found as the polynomial of n-th degree named Expression 4. The least-square method is used to calculate coefficients b_k in Expression 2 (S40).

$$L = \sum_{k=0}^n b_k x^k \quad \dots (4)$$

(x: area rate, L: 8-bit output gradation level)
FIG. 12 shows an example of a curve representing the relationship between the 8-bit output gradation level and estimated area rate. Gradation correction table values are calculated by dividing the area rate axis into 256 equal segments and finding the 8-bit gradation level corresponding to each division point using Expression 4.

Finally, using the flowchart for creating a color conversion table of FIG. 8, a procedure for creating a color conversion table is described below. First, a patch image for creating color conversion table is output (S51). Patch data for creating a color conversion table is stored in the patch data memory C. The patch data, representing a 8-bit area rate each for C, M, and Y, is set so that a plurality of patches are laid out which are provided by combining C, M, and Y when the area rate is changed at regular intervals. The patch image creator C creates patch image data for creating a color conversion table, using the patch data. FIG. 13 shows an example of arrangement of patches for creating a color conversion table. The patch image data is fed to the blackening unit. In response to a control signal from the image processing controller, the blackening unit selects image data from the patch image creator C as input. After subjected to blackening (S52), gradation correction using the above-described set gradation correction table (S53), quasi intermediate gradation processing (S54), pulse width selection using the above-described set pulse width selection table (S55), and screen processing (S56), the patch image data is output onto paper (S57).

Then the output patch image for creating a color conversion table is read by the scanner (S58). In this case, the input γ characteristics of the preprocessor

are set for ordinary copying (S59). This is both because for color conversion, RGB data itself fed from the preprocessor is input and because starting the procedure shown by the table creation flowchart with the patch data representing the area rate eliminates the need for area rate estimation. After subjected to preprocessing, patch image data input from the scanner is fed to the patch data extractor 53 (S60). Based on preset information on patch print layout, the patch data extractor 55 samples pixel data to extract the R, G, and B values of each patch. To cancel the effect of noise, many pixels in rectangular formation are cut out of the middle of a patch, and the total of them is calculated. Each of the R, G, and B values is divided by the number of pixels cut to take an average (FIG. 10).

Finally, the color conversion table setting unit 54 creates a color conversion table, based on the extracted patch data and patch data which is stored in the patch data memory C. The RGB-CMY color conversion relationship is approximately found as the matrix equation named Expression 5 (S62). The least-square method is used to calculate color conversion matrix elements D_{ij} in Expression 5.

$$\begin{bmatrix} C \\ M \\ Y \end{bmatrix} = \begin{bmatrix} D_{00} & D_{01} & D_{02} & D_{03} & D_{04} & D_{05} & D_{06} & D_{07} & D_{08} & D_{09} \\ D_{10} & D_{11} & D_{12} & D_{13} & D_{14} & D_{15} & D_{16} & D_{17} & D_{18} & D_{19} \\ D_{20} & D_{21} & D_{22} & D_{23} & D_{24} & D_{25} & D_{26} & D_{27} & D_{28} & D_{29} \end{bmatrix} \begin{bmatrix} R \\ G \\ B \\ R^2 \\ G^2 \\ B^2 \\ RG \\ GB \\ BR \\ 1 \end{bmatrix} \dots (5)$$

Color conversion values are calculated by dividing the RGB color space into equal portions at right angles to each axis and finding C, M, and Y values corresponding to the RGB coordinates of each division grid point.

The pulse width selection table, gradation correction table, and color conversion table are created in that order. That is, these tables are sequentially created, one which has the lowest degree of freedom and can be created according to the simplest policy first, and then tables which have higher degree of freedom are created, taking the already created table into account. Although the number of gradation levels is limited to, for example, 16, a pulse width selection table is created according to a simple, easy-to-keep rule that a laser drive pulse width is assigned so that the record area rate linearly changes for each level. Thus gradation resolution can be kept good over the entire density range.

Based on patch data stored in the storage area using such an arrangement, patch image data is output,

and patch data is extracted from reading patch data
read by a scanner or the like from a reading patch
image formed according to the patch image data. An
image processing apparatus which makes gradation
5 correction best suited for the equipment possible is
provided by estimating record gradation from the patch
data. Moreover, a digital copying machine using the
image processing apparatus provides high gradation and
color reproducibility.

10 Because image processing controlling means are
provided which switch input γ characteristics set for
ordinary copying to linear input γ characteristics
during preprocessing preceding patch data extraction,
the present invention makes it possible to estimate the
15 area rate necessary for table creation with high
accuracy when a patch image is read using a scanner to
create pulse width selection table and a gradation
correction table.

<Conclusion>

20 As described above, the present invention makes it
possible to estimate gradation more accurately by
selecting gradation information, such as the area
rate, gradation density, or a combination of these,
from patch data as the case may be and referring
25 to created tables. Thus gradation characteristic
variations from equipment to equipment are corrected
accurately, providing a color image processing

apparatus which allows gradation and color to be reproduced well.

Based on a gradation estimated in such a manner, image processing parameter tables, that is, a pulse width selection table, a gradation correction table, and a color conversion table are created in that order. By doing so, the adjustable parameter tables can be dispersively provided at a plurality of key points in an image processing flowchart to create each table according to a relatively simple target or rule, so that image processing parameters can easily be obtained to reproduce gradation and color well.

Because image processing controlling means are provided which switch input γ characteristics set for ordinary copying to linear input γ characteristics during preprocessing preceding patch data extraction, the present invention makes it possible to estimate the area rate necessary for table creation with high accuracy when a patch image is read using a scanner to create pulse width selection table and a gradation correction table.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the

spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

005230" 63574260

WHAT IS CLAIMED IS:

1. A color image processing apparatus comprising:
patch image output means for outputting patch
image data generated from patch data stored in storage
5 areas;

patch data extracting means for receiving read
data obtained by reading, by means of a scanner, a
patch image which is formed corresponding to the patch
image data output from the patch image data output
10 means, and extracting a read patch data from the read
data;

gradation estimating means for estimating a record
gradation of the patch data on the basis of the read
patch data extracted by the patch data extracting
15 means; and

correction output means for correcting an input
color image signal on the basis of the record gradation
estimated by the gradation estimating means and the
patch data stored in the storage area, and for
20 outputting the corrected signal.

2. A color image processing apparatus according
to claim 1, wherein the gradation estimating means and
correction output means include:

pulse width selection table setting means for
25 estimating the record gradation of the patch data on
the basis of the read patch data extracted by the patch
data extracting means and for setting a pulse width

005530" 68554960

selection table on the basis of the estimated record gradation and the patch data stored in the storage area; and

5 pulse width output means for selecting a pulse width based on the pulse width selection table set by the pulse width selection table setting means, and for outputting an input color image signal in accordance with the selected pulse width.

10 3. A color image processing apparatus according to claim 1, wherein the gradation estimating means and correction output means include:

15 gradation correction table setting means for estimating the record gradation of the read patch data on the basis of the read patch data extracted by the patch data extracting means, and for setting a gradation correction table on the basis of the estimated record gradation and the patch data stored in the storage area; and

20 gradation correction output means for correcting the gradation of an input color image signal on the basis of the gradation correction table set by the gradation correction table setting means, and for outputting the corrected color image signal.

25 4. A color image processing apparatus according to claim 1, wherein the gradation estimating means and correction output means include:

pulse width selection table setting means for

005230" 68554960

estimating the record gradation of the read patch data
on the basis of the read patch data extracted by the
patch data extracting means and for setting a pulse
width selection table on the basis of the estimated
5 record gradation and the patch data stored in the
storage area;

second patch image output means for outputting
second patch image data, by using the pulse width
selection table set by the pulse width selection table
10 setting means, corresponding to the second patch data
for creating a gradation correction table which is
stored in a second storage area;

second patch data extracting means for receiving
second read data obtained by reading, by means of a
15 scanner, a second patch image which is formed
corresponding to the second patch image data output
from the second patch image output means, and for
extracting second read patch data from the second patch
image;

20 second gradation estimating means for estimating
gradation of the second read patch data on the basis of
the second read patch data extracted by the second
patch data extracting means;

gradation correction table setting means for
25 setting a gradation correction table on the basis of
the record gradation of the second read patch data
estimated by the second gradation estimating means and

005530" 66557960

the second patch data; and

correction output means for correcting an input color image signal on the basis of the pulse width selection table set by the pulse width selection table setting means and the gradation correction table set by the gradation correction table setting means, and for outputting the corrected signal.

5. A color image processing apparatus according to claim 2, wherein the pulse width selection table setting means includes

pulse width selection table setting means for pre-processing the read patch data extracted by the patch data extracting means after changing ordinary input γ characteristic settings to linear settings, for estimating the record gradation of the patch data from the preprocessed read patch data, and for setting a pulse width selection table on the basis of the estimated record gradation and the patch data stored in the storage area.

6. A color image processing apparatus according to claim 3, wherein the gradation correction table setting means includes pulse width selection setting means for pre-processing the read patch data extracted by the patch data extracting means after changing ordinary input γ characteristic settings to linear settings, for estimating the record gradation of the read patch data from the preprocessed read patch data,

and for setting a gradation correction table on the basis of the estimated record gradation and the patch data stored in the storage area.

7. A color image processing apparatus according to claim 1, wherein the gradation estimating means includes

gradation estimating means for finding C, M, Y, and K record area rates on the basis of the given read patch data and for estimating the record gradation of the patch data on the basis of the found C, M, Y and K record area rates.

8. A color image processing apparatus according to claim 1, wherein the gradation estimating means includes

gradation estimating means for finding C, M, Y, and K record densities on the basis of the given read patch data and for estimating the record gradation of the patch data on the basis of the found C, M, Y and K record densities.

9. A color image processing apparatus according to claim 1, wherein the gradation estimating means includes

gradation estimating means for estimating the record gradation of the patch data by receiving the estimated density from a density estimator estimating the density and the area rate from an area rate estimator estimating the area rate, based on the given

005280 6854960

read patch data, and for outputting one of the estimated density and the area rate.

10. A color image processing apparatus according to claim 1, wherein the gradation estimating means
5 includes

means for estimating record gradation by receiving a plurality of pieces of estimated gradation information from a plurality of gradation estimators estimating record gradation on the basis of the given
10 read patch data, using reference tables, and by selecting and outputting one of the pieces of estimated gradation information.

11. A color image processing apparatus comprising:

first patch image output means for outputting
15 first patch image data on the basis of the first patch data for creating a pulse width selection table stored in the first storage area;

first patch data extracting means for reading, using a scanner, a first patch image which is formed
20 corresponding to first patch image data output from the first patch image output means, and for extracting first patch data in accordance with the first patch image;

first gradation estimating means for estimating
25 record gradation of the first read patch data, from the first read patch data extracted by the first patch data extracting means;

005220" 68554950

pulse width selection table setting means for
setting a pulse width selection table on the basis of
the record gradation of the first read patch data
estimated by the first gradation estimating means and
5 the first patch data;

second patch image output means for outputting
second patch image data, using the pulse width
selection table set by the pulse width selection table
setting means, corresponding to the second patch data
10 for creating a gradation correction table stored in the
second storage area;

second patch data extracting means for reading,
using a scanner, a second patch image which is formed
corresponding to the second patch image data output
15 from the second patch image output means, and for
extracting second read patch data in accordance with
the second patch image;

second gradation estimating means for estimating
the record gradation of the second read patch data on
20 the basis of the second read patch data extracted by
the second patch data extracting means;

gradation correction table setting means for
setting a gradation correction table on the basis of
the record gradation of the second read patch data
25 estimated by the second gradation estimating means and
the second patch data;

third patch image output means for outputting

005230 685490

third patch image data, using the pulse width selection table set by the pulse width selection table setting means and the gradation correction table set by the gradation correction table setting means and on the basis of the third patch data for creating a color conversion table stored in a third storage area;

third patch data extracting means for reading, using a scanner, a third patch image represented by third patch image data output by the third patch image output means, and for extracting third patch data according to the third read patch image;

color conversion table setting means for setting a color conversion table on the basis of the third read patch data extracted by the third patch data extracting means and the third patch data; and

correction output means for correcting a given and input color image signal on the basis of the pulse width selection table set by the pulse width selection setting means, the gradation correction table set by the gradation correction table setting means, and the color conversion table set by the color conversion table setting means, and for outputting the corrected signal.

12. A color image processing apparatus according to claim 11, wherein the pulse width selection table setting means include

pulse width selection setting means for

005230 68534960

pre-processing the read patch data extracted by the patch data extracting means after changing ordinary input γ characteristic settings to linear settings, for estimating the record gradation of the read patch data from the preprocessed read patch data, and for setting a gradation correction table on the basis of the estimated record gradation and the patch data stored in the storage area; and

wherein the gradation correction table setting means include gradation correction table setting means for pre-processing the read patch data extracted by the patch data extracting means after changing ordinary input γ characteristic settings to linear settings, for estimating the record gradation of the read patch data from the preprocessed read patch data, and for setting a gradation correction table on the basis of the estimated record gradation and the patch data stored in the storage area.

13. A color image processing apparatus according to claim 11, wherein the gradation estimating means includes

gradation estimating means for finding C, M, Y, and K record area rates on the basis of the given read patch data and for estimating the record gradation of the patch data from the area rates.

14. A color image processing apparatus according to claim 11, wherein the gradation estimating means

includes

gradation estimating means for finding C, M, Y,
and K record densities on the basis of the given read
patch data and for estimating the record gradation of
the patch data from the densities.

15. A color image processing apparatus according
to claim 11, wherein at least one of the first and
second gradation estimating means includes

gradation estimating means for estimating the
record gradation of the patch data by receiving the
estimated density from a density estimator estimating
the density and on the basis of the given read patch
data and the area rate supplied from an area rate
estimator estimating the area rate, and for outputting
one of the estimated density and the area rate.

16. A color image processing apparatus according
to claim 11, wherein at least one of the first and
second gradation estimating means includes

means for estimating record gradation by receiving
a plurality of pieces of estimated gradation
information from a plurality of gradation estimators
estimating record gradation from the given read patch
data and selecting and outputting one of the pieces, by
using reference tables.

17. A color image forming apparatus comprising:
a color scanner for reading a color image from a
given original and outputs color image data;

a color printer for forming an image on
a recording medium in accordance with the given color
image data;

5 patch image forming means for forming a patch
image on the recording medium in accordance with a
patch data stored in storage areas, by using the image
forming means;

10 patch data extracting means for extracting read
patch data from image data obtained by reading the
patch image formed by the patch image forming means,
using the color scanner;

15 gradation estimating means for estimating record
gradation of the patch data on the basis of the read
patch data extracted by the patch data extracting
means;

correction output means for correcting a given and
input color image signal on the basis of the record
gradation estimated by the gradation estimating means
and the patch data stored in the storage area; and

20 forming means for forming an image on a recording
medium, using a color printer, in accordance with the
color image signal corrected and output from the
correction output means.

18. A color image forming apparatus comprising:

25 a color scanner for reading a color image from a
given original and for outputting color image data;

a color printer for forming an image on a

005280" 6854963

recording medium in accordance with the color image data;

first patch image forming means for forming, using the color printer, first patch image on a recording medium in accordance with the first patch data for creating a pulse width selection table, which is stored in first storage area;

first patch data extracting means for extracting first read patch data from the read image data obtained by reading, using the color scanner, the first patch image formed by the first patch image forming means;

first gradation estimating means for estimating record gradation of the first read patch data on the basis of the first read patch data extracted by the first patch data extracting means;

pulse width selection table setting means for setting a pulse width selection table on the basis of the record gradation of the first patch data estimated by the first gradation estimating means;

second patch image forming means for forming a second patch image on a recording medium using the color printer and the pulse width selection table set by the pulse width selection table setting means on the basis of the second patch data for creating a gradation correction table stored in the second storage area;

second patch data extracting means for extracting second read patch data from read image data obtained by

0055230" 6854960

reading, using the color scanner, the second patch
image output by the second patch image forming means;

second gradation estimating means for estimating
record gradation of the second read patch data on the
5 basis of the second read patch data estimated by the
second patch data extracting means;

gradation correction table setting means for
setting a gradation correction table on the basis of
the record gradation of the second read patch data
10 estimated by the second gradation estimating means and
the second patch data;

third patch image output means for forming a third
patch image on a recording medium with the color
printer, using the pulse width selection table set by
15 the pulse width selection table setting means and the
gradation correction table set by the gradation
correction table setting means on the basis of third
patch data for creating a color conversion table stored
in the third storage area;

20 third patch data extracting means for extracting
third read patch data from read image data obtained by
reading a third patch image formed by the third patch
image forming means, using the color scanner;

color conversion table setting means for setting a
25 color conversion table on the basis the third read
patch data extracted by the third patch data extracting
means and the third patch data;

005280" 6854960

correction output means for correcting an input
color image signal on the basis of the pulse width
selection table set by the pulse width selection
setting means, the gradation correction table set by
5 the gradation correction table setting means, and the
color conversion table set by the color conversion
table setting means and output the corrected signal;
and



forming means for forming, using the color printer,
10 an image on a recording medium in accordance with the
color image signal corrected and output by the
correction output means.

005230" 68554960

ABSTRACT OF THE DISCLOSURE

5 A color image processing apparatus having at least
patch image output units which output patch image data,
based on patch data in a storage area, a patch data
extractor which extracts read patch data by reading a
patch image formed according to the patch image data,
using a color scanner, a patch data processor which
estimates the record gradation of patch data, based on
the read patch data, and a gradation corrector which
10 corrects a given color image signal, based on the
estimated record gradation and patch data. The
apparatus provides gradation correction based on
gradation estimated from patch data, thus making it
possible to reproduce gradation and color well.


005280" 682480




```

graph TD
    START([START]) --> S11[PREPROCESSING INPUT  
γ CHARACTERISTIC  
IS MADE LINEAR]
    S11 --> S12[PULSE WIDTH  
SELECTION TABLE IS  
CREATED]
    S12 --> S13[GRADATION(OUTPUT γ)  
CORRECTION TABLE IS  
CORRECTED]
    S13 --> S14[PREPROCESSING INPUT  
γ CHARACTERISTIC IS  
RETURNED TO  
SPECIFIED SETTING]
    S14 --> S15[COLOR CONVERSION  
TABLE IS CREATED]
    S15 --> END([END])

```






FIG. 7





FIG. 8

FIG. 9



SQUARE
READING
REGION




FIG. 10




FIG. 11




FIG. 12




FIG. 13

DECLARATION FOR PATENT APPLICATION

As a below named inventor, I declare:
that I verily believe myself to be the original, first and sole (if only one individual inventor is listed below) or an original, first and joint inventor (if more than one individual inventor is listed below) of the invention in

COLOR IMAGE PROCESSING APPARATUS AND COLOR IMAGE
FORMING APPARATUS

the specification of which is attached hereto unless the following box is checked.

☐ was filed on _____ as United States Application
or PCT International Application No. _____, and
was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information of which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365 (b) of any foreign application(s) for patent or inventor's certificate, or 35 U.S.C. 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed:

<u>Country</u>	<u>Category</u>	<u>Application No.</u>	<u>Filing Date</u>	<u>Priority Claim</u>
Japan	Patent	11-242119	August 27, 1999	Yes

And I hereby appoint Stephen A. Bent (Reg.No. 29,768), David A. Blumenthal (Reg.No. 26,257), William T. Ellis (Reg.No. 26,874), John J. Feldhaus (Reg.No. 28,822), Patricia D. Granados (Reg.No. 33,683), John P. Isacson (Reg.No. 33,715), Eugene M. Lee (Reg.No. 32,039), Richard Linn (Reg.No. 25,144), Peter G. Mack (Reg.No. 26,001), Brian J. McNamara (Reg.No. 32,789), Sybil Meloy (Reg.No. 22,749), George E. Quillin (Reg. No. 32,792), Colin G. Sandercock (Reg.No. 31,298), Bernhard D. Saxe (Reg. No. 28,665), Charles F. Schill (Reg.No. 27590), Richard L. Schwaab (Reg. No. 25,479), Arthur Schwartz (Reg.No. 22,115) and Harold C. Wegner (Reg. No. 25,258), each of whose address is Suite 500, 3000 K Street, N.W. Washington, D.C. 20007-5109, or any one of them, my attorneys with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent & Trademark Office connected therewith, and request that correspondence be directed to Foley & Lardner, Suite 500, 3000 K Street, N.W. Washington, D.C. 20007-5109.

I declare further that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

I declare further that my citizenship, residence and post office address are as stated below next to my name:

Inventor: (Signature)

Date _____

Residence and post office address

Date: August 17, 2000

7-2-704, Ebara 3-chome,

Citizen of: Japan

Shinagawa-ku, Tokyo, Japan

Takayuki Sawada
Takayuki Sawada

513, Toshiba Shinkoyasu Dai-1 Ryo,

Date: August, 17, 2000

214-10, Shinkoyasu 2-chome,

Citizen of: Japan

Kanagawa-ku,

Yokohama-shi, Kanagawa-ken, Japan

Shinsaku Ito
Shinsaku Ito

Date:

Citizen of: Japan

Date:

Citizen of: Japan

Date:

Citizen of: Japan

Date:

Citizen of: Japan

Date:

Citizen of: Japan

Date:

Citizen of: Japan

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Takayuki SAWADA *et al.*
Title: COLOR IMAGE PROCESSING APPARATUS AND
COLOR IMAGE FORMING APPARATUS
Appl. No.: Not yet assigned
Filing Date: August 25, 2000
Examiner: Not yet assigned
Art Unit: Not yet assigned


ASSOCIATE POWER OF ATTORNEY

Sir:

The undersigned attorney of record hereby grants Johnny A. Kumar, Reg. No. 34,649, an associate power with full powers of substitution and revocation to prosecute the above-identified application and transact all business in the Patent and Trademark Office connected therewith.

Respectfully submitted,

August 25, 2000
Date



William T. Ellis
Reg. No. 26,874

FOLEY & LARDNER
3000 K Street, NW, Suite 500
P.O. Box 25696
Washington, DC 20007-8696
Telephone: (202) 672-5300
Facsimile: (202) 672-5399